

## SADP ツールを使ったパスワードリセット

■必要なもの

- ・SADP ツール
- ・パソコン
- ・LAN ケーブル

以下のダウンロードサイトから「SADP ツール」をダウンロードしてください。 https://hik.dss.co.jp/support/download

iVMS4200(3.0)	
NMS4200(3.5.0.4) ソフトウェア  NMS4200 ユーザーマニュアル  NMS4200 陰陽マニュアル  NMS4200 陰陽マニュアル	
WMS4200 Hik-Connectマニュアル WMS4200 シーケンス(自動切り替え)マニュアル	
1VMS4200 AC	
■ NMS4200 AC(1.5.0.4) ソフトウェア WMS42007クセスコントロール操作マニュアル	
動画再生ソフト	
VSPlayer (V7.3.0)	
IP検索'ツール	
SADP (V3.0.2.4)	
録画日数計算ソフト	
Storage and Network Calculator	
各種詳細マニュアル	
IPC_初期化方法 IPC_アクセス(IPアドレス変更、パスワード変更)	
Hilandaian ハイクビジョン国内ERNOTBA(アイーズセキュリフィBALC名)> サポート > ダクンロード	
製品機能 ダウンロード ハイクビジョン 得入事件 分配着家みショールーム ニョースリリース 第1日本イントッチ	

1.パソコンとパスワードリセットを行うデバイスを同じネットワークに接続します。



LANケーブル



## 2.SADP ツールを起動し、パスワードリセットを行うデバイスにチェックを入れて、 [Forgot Password]をクリックします。

SADF	0											\$30 _ D ×
Total nun	ber of online device	8				Unbind	Export	Refresh	Filter	Q	Modify Network Parame	iters
•	ID	-   Device Type	Status	IPv4 Address	Port	Enhanced SD	Software Vers	IPv4 Gateway	HTTP Port	Device Serial	Enable DHCP     Enable Hik-Connect	
	001	DS-K1TA70M	Active	100000000000000000000000000000000000000	8000	N/A	V2.2.6build 2	192.168.1.1	80	DS-K1TA70N		
2	002	DS-7616NI-I	Active	100.000	8000	8443	V4.40.010buil	0.0.0.0	80	DS-7616NI-I	Device Serial No.:	DS-7616NI-12/16P1620200326CCF
<b>P</b>	003	DS-KC001	Active	-	8000	N/A	V2.1.9build 2	192.168.1.1	80	DS-KC00101.	IP Address:	192.168.1.200
	004	DS-2TD1217	Active	100.000	8000	N/A	V5.5.32build	192.168.1.1	80	DS-2TD1217	Ports	8000
	005	EX-2121G1	Active	100,0001-00	8000	8443	V5.5.92build	192.168.1.1	80	EX-2121G1	Enhanced SDK Service Port:	8443
	006	EX-2121G1	Active	100,000,000	8000	8443	V5.5.92build	192.168.1.1	80	EX-2121G1	Subnet Mask:	255.255.255.0
	007	EX-2121G1	Active	10000	8000	8443	V5.5.92build	192.168.1.1	80	EX-2121G12.	Gateway	0.0.0.0
	008	EX-2121G1	Active		8000	8443	V5.5.92build	192.168.1.1	80	EX-2121G12.	IPv6 Address:	fe80::9adf:82ff:fed8:ae88
											IPu6 Gateway	
					$\searrow$						ID-6 Drofy Leosth	
											IPV0 Prenx Length:	04
											HTTP Ports	80
											Secu	rity Verification
								<				
											Admin Password:	
												Mindlify
												Forget Password
												- orgot Password

## 3.① の箇所から「Export」をクリックしてパスワードリセットファイルの保存先を指定します。

Und und     Image: Control of the	SADP											\$t0 _ 5 ×
Image: Control Type       Bute       MA Address       Rest       Ended DHC2       Ended DHC2         Image: Control Type       Bute       Made       Image: Control Type       Bute       Image: Control Type       Bute       Image: Control Type       Bute       Image: Control Type       Bute       Image: Control Type       Image: Contro Type       Image: Contro Type       Image: Con	Total numb	ber of online device	. 8			Unbind	Export	Refresh		Q	I Modify Network Parame	ters
00 05-K11020ML Advie   000 05-K1020ML		1 ID	-   Device Type	Status	IPv4 Address   Port	Enhanced SD	Software Vers	IPv4 Gateway	HTTP Port	Device Serial	Enable DHCP	
02       05.72(08):L. Advie       Mode:       Eport/Import Secret Kay Mode •       001       Device Sinik Acce 05.72(08):L. Advie       003       05.42(03)       Advie       003       05.22(10)       Advie       003		001	DS-K1TA70M	Active						× TA70N		
03 054001 4dre   04 05270277. Adre   05 05212101 Adre   05 05221210 Adre   06 05221201 Adre   070 05232101 Adre   080 05221201 Adre   080 05222101   080 0522201 <t< td=""><td>2</td><td>002</td><td>DS-7616NI-I</td><td>Active</td><td>Modes</td><td>Export/Import S</td><td>Secret Key Mode 👻</td><td></td><td></td><td>16NI-L</td><td>Device Serial No.:</td><td>DS-7616NI-12/16P1620200326CCF</td></t<>	2	002	DS-7616NI-I	Active	Modes	Export/Import S	Secret Key Mode 👻			16NI-L	Device Serial No.:	DS-7616NI-12/16P1620200326CCF
004 05-210127. Active   005 05/212101 Active   006 05/212101 Active   007 05/212101 Active   008 05/212101 Active   008 05/212101 Active   009 05/212101 Active   009 05/212101 Active   009 05/212101   019 Addres   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/212101   019 05/2		003	DS-KC001	Active	Step 1: Click Export	to download the key	request file (XML fil	le) or		00101.	(P Address:	192.168.1.200
003       EX212101       Active         004       EX212101       Active         005       EX212101       Active         006       EX212101       Active         007       EX212101       Active         008       EX212101       Active         008       EX212101       Active         008       EX212101       Active         009       Input Key       Input Key         009       Extended SDK Service New       Eddid         009       Input Key       Input Key         009		004	DS-2TD1217	Active	take a photo of the	QR code. Send the XI	ML file or QR code	photo to		D1217	Ports	8000
06       EX-21216       Attive       Export       Cit code       Fig.         07       EX-212161       Attive       Stape 2: Input the kay of inport the kay file received from the technical engineer to reset the password for the device.       Fig.       Fig.<		005	EX-2121G1	Active						2161	Enhanced SDK Service Port	8443
007 EX-212101 Active   008 EX-212101 Active     019 EX-212101     019 Extended     019 Extended     020 Extended     02101 Extended     0211 Extended     0211 Extended     0212 Extended        0212 Extended                    0212 Extended		006	EX-2121G1	Active	Export	QR code				21G1	Subpet Mask:	
05       EX212101       Active       engineer to reset the password for the device.       1012       104 Address       104 Addres       104 Add	-	007	EX-2121G1	Active	Step 2: Input the ke	y or import the key fil	le received from the	technical		21612		
Input Key Import File   Input Key Import File   New Password: Import File   Confirm Password: Import File   Confirm Cancel ItTTP Pert:   Bo ItTTP Pert:   Bo<	10	008	EX-2121G1	Active	engineer to reset th	e password for the d	evice.			21612.	Galeway.	
Input Key Import File   Input Key Import File   New Password: Import File   Confirm Password: Import File   Reset Network Cameras' Passwords: Security Writication   Confirm Cancel Admin Password:											IPv6 Address:	fe80::9adf:82ff:fed8:ae88
Image: Second					• Input Key	Import File					IPv6 Gateway:	
New Password:					-						IPv6 Prefix Length:	64
Confirm Password: Confirm Passwords. Confirm Cancel					New Password:					1.00	HTTP Ports	80
Confirm       Security Varification         Confirm       Confirm         Confirm       Cancel												
					Confirm Password							
Confirm       Cancel         Confirm       Cancel         Admin Password:       Admin Password:         Modly       Forgot Password:					🗌 Reset Network C	ameras' Passwords						
Condition     Condition       Admin Password:					_			-				
Admin Password:  Modily  Forgot Password  Forgot Password									Confirm	ancel		
Admin Pessword:  Admin Pessword:  Modily  Forgot Pessword  Forgot Pessword												
Admin Pessword:												
Modily Forget Password											Admin Password:	
Modily Forgot Password												
Forget Pasword												Modify
												Forget Password



4. 1 抜き出したパスワードリセットファイルを担当者に送ります。

※パスワードリセットファイルを抜き出した後は、パスワードリセットを行うまで、 パソコンやデバイスの電源を切ったり、再起動はしないでください。

5.パスワードリセットファイル返却後、②の箇所から「Input Key」→「Import Key」に切り替え、 ファイルマークをクリックして、保存先から返却されたパスワードリセットファイルを指定します。

SADP											
Total numb	er of online devices:	8			Unbind	Export	Refresh		Q	I Modify Network Parame	ters
	1 ID -	Device Type	Status	IPv4 Address   Port	Enhanced SD.	Software Vers	.  IPv4 Gateway	HTTP Port	Device Serial	Enable DHCP	
	001	DS-K1TA70M	Active	8000	N/A	V2.2.6build 2	192.168.1.1	80	DS-K1TA70N	Enable Hik-Connect	
2	002	DS-7616NI-I	Active	Reset Password					× 6NI-I	Device Serial No.2	DS-7616NI-12/16P1620200326CCF
	003	DS-KC001	Active	Mode:	Export/Impor	rt Secret Key Mode			0101.	IP Address:	192.168.1.200
	004	DS-2TD1217	Active	1 Step 1: Click Export	to download the ke	ey request file (XM	L file) or		1217	Port	8000
	005	EX-2121G1	Active	our technical engine	ers.	AML file of QK co	de photo to		1G1	Enhanced SDK Service Port:	8443
	006	EX-2121G1	Active	Export	QR code				161	Subnet Mask:	255.255.255.0
	007	EX-2121G1	Active						1G12.	Gateway:	0.0.0.0
	008	EX-2121G1	Active	Step 2: Input the key engineer to reset the	y or import the key e password for the	file received from device.	the technical		1G12,	IPv6 Address:	fe80:9adf:82ff:fed8:ae88
				_						IDu6 Gateway	
				🔿 Input Key 🕚	Import File	<u> </u>				in to obtendy.	
										IPVO Pretix cengui:	04
				New Password:						HTTP Ports	80
				Confirm Password:							
				Reset Network Ci	ameras' Passwords						
									_		
								Confirm	ancel		
										Admin Password:	
											Modify
											Forgot Password

- 6.「New Password」の箇所に新しく設定するパスワードを入力します。
  - 「Confirm Password」の箇所に「New Password」で入力したパスワードを再度入力します。 すべてのパスワード入力後、「Confirm」をクリックしてパスワードリセットを完了します。

